

DigiX

Keypad

Intro

A heavy duty DMR Digital/Analogue radio the original DigiX is professional and well respected with a high IP rating of IP67 which provides for a reliable radio in demanding environments. The DigiX is a well proven and In demand radio for many customers across the UK. The DigiX is a high power portable allowing for a maximum range provided across many demanding sites. A wide choice of accessories and charger options are available off the shelf for immediate delivery.

The DigiX radio is also available as a standard version without keypad/display.



Features

Available in VHF or UHF frequency

Single, group or all call function

IP67 water and dust protection

VOX on/off function

Digital mode SMS function

Voice encryption

Up to 1000 channels

Message edit

One touch access

Double priority channel scan

Digital power saving mode

Remote monitor

Stun / revive

Emergency Caller

Caller Identification.



Design and Manufacture

Specs

Frequency Range	400-470Mhz/136-174Mhz
Channel Capacity	32
Normal Operating Voltage	7.4V
Operating Temperature	-20°C - +60°C
Store Temperature	-40°C - +85°C
Weight	270g(include Li-ion battery)
Dimensions:H*W*D(mm)	113.5 x 54 x 33.5mm
Dust-protection and water resistant	IP67
1800mAh Standard Li-ion battery	Analog:10 hours; Digital:14 hours

Transmitter

Channel Spacing	12.5Khz
Frequency Stability	±1.0ppm
Power	Low Power:1W; High Power:4W
Hum and Noise	-40dB@12.5Khz
Ajacent Channel Power	-60dB@12.5Khz
Ajacent Transient Channel Power	-50dB@12.5Khz
FM Modulation Mode	12.5Khz:11K0F3E
Audio Response	+1dB - -3dB
Audio Distortion	3%(Type)
Digital Protocol	ETSI TS 102 361-1,-2,-3
Vocoder Type	AMBE+2

Receiver

Channel Spacing	12.5Khz
Frequency Stability	±1.0ppm
Analog Sensitivity	0.35uV/-116dBm(20 dB SINAD) 0.22uV/-120dBm(Type)
Digital Sensitivity	0.3uV/-117dBm(BER5%) 0.7uV/-110dBm(BER 1%)
Intermodulation	TIA603C:70dB ETSI:65dB
Ajacent Channel Sensitivity	TIA603C:65dB@12.5Khz ETSI:60dB@12.5Khz
Co-Channel rejection	12dB@12.5Khz
Spurious Response rejection	TIA603C:75dB ETSI:70dB
Conducted Spurious emission	-57dBm@<1GHz,-47dBm@1GHz
Bloking	84dB
Rated Audio Power	1W

Accessories



Antenna



Lithium Battery



Belt Clip



Charger



Strap

All specifications are subject to change without notice due to continuous development.

Contact us today

0800 195 5919 | sales@nrcradio.co.uk

nrcradio.co.uk

DigiX